

Type

Aromatic-free hydrocarbon solvent.

User-friendlier alternative to petroleum spirit and turpentine.

Intended use

For thinning of Uula Door and Window Paint, Uula Glazing Oil Paint, Uula Eggshell Interior Oil Paint, oil based decorative paints (e.g. marbling, graining etc.) and Uula Linseed Oil Paint in interior surfaces.

Also for cleaning the equipment and removing different stains such as pitch, tar, grease etc.

Technical qualities

Density approx. 0.85kg/L.

Container size

1 L, 3 L and 10 L.

Storage & disposal

Keep in a cool place. Keep out of the reach of children. Do not allow to freeze.

Dry and empty containers can be taken to a refuse dump.

Liquid waste must be taken to a municipal hazardous waste collection point

Fire classification

Non-flammable.

In case of uncertainty, submit to the manufacturer of the paint or to a competent distributor before starting the painting process.

Information in the technical specification is based on tests and practical experience. All instructions are only indicative and depend, for example, on the texture of the surface, quality, colour and previous treatments. Because we cannot control the use and working conditions of our products we take responsibility only for the quality of the product and guarantee that it is in accordance with the high standards of Uulatuote Oy. We do not take responsibility for damage caused by using the product against our instructions or intended use.