

Type

Alkaline washing agent for cleaning dirty surfaces before painting, pH8.
Suitable to use in all interior and exterior surfaces before painting.
Removes dirt, soot, grease etc. effectively and creates a good, clean surface for re-painting.

Intended use

For interior and exterior use on walls, roofs, ceilings, furniture etc. before painting.

Technical qualities

Density approx. 1 kg/L.

Dosage instructions:

Dosage in water

Extremely dirty surfaces: 1:10 – 1:20.

Dirty surfaces: 1:20-1:40.

Slightly dirty surfaces: 1:40 – 1:100.

Can be used undiluted for removing stains.

Treatment instructions

Apply on to the surface with a sponge, a cloth, a brush or a low-pressure spray.

Let it affect approximately 10 min and rinse with warm water.

Scrub or brush if the surface is extremely dirty.

Container sizes

1 L and 5 L

Storage & disposal

Keep in a cool place. Keep out of the reach of children. Do not allow to freeze.

Dry and empty containers can be taken to a refuse dump.

Liquid waste must be taken to a municipal hazardous waste collection point

Fire Classification

Non-flammable.

Points to note:

*Allow the cleaned surfaces to dry thoroughly before painting.

*Uula Washing Agent may tarnish glossy surfaces if used undiluted.

*In case of uncertainty, submit to the manufacturer of the paint or to a competent distributor before starting the painting process.

Information in the technical specification is based on tests and practical experience. All instructions are only indicative and depend, for example, on the texture of the surface, quality, colour and previous treatments. Because we cannot control the use and working conditions of our products we take responsibility only for the quality of the product and guarantee that it is in accordance with the high standards of Uulatote Oy. We do not take responsibility for damage caused by using the product against our instructions or intended use.