



Uula Floor Paint
Uula Door and Window Paint

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** Uula Floor Paint
Uula Door and Window Paint
- Other means of identification:**
- UFI:** QM80-20HH-S00V-071A
- 1.2 Relevant identified uses of the substance or mixtures and uses advised against:**
Relevant uses: Paint
Uses advised against: All uses not mentioned in this section or in section 7.3.
- 1.3 Details of the supplier of the safety data sheet:**
Uula Color Oy
Yttiläntie 265
32920 Kauvatsa, Finland
Tel: +358 10 820 0020
uula@uula.fi
<http://www.uula.fi>
- 1.4 Emergency telephone number:** 0800-147 111 (toll-free number), +358 (0)9-471 977 (direct), +358 (0)9-4711 (switchboard), Poison Information Center

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of a substance or mixture:**
CLP Regulation (EC) No 1272/2008:
This product is classified in accordance with CLP Regulation (EC) No 1272/2008.
Aquatic Chronic 3: Hazardous to the aquatic environment, chronic hazard, category 3, H412
Skin Sens. 1A: Sensitisation, skin, Category 1A, H317
- 2.2 Label elements:**
CLP Regulation (EC) No 1272/2008:
Warning

Hazard statements:
Aquatic Chronic 3: H412 - Harmful to aquatic organisms with long-term adverse effects.
Skin Sens. 1A: H317 - May cause an allergic skin reaction.
Precautionary statements:
P101: If medical assistance is required, show the package or the warning label.
P102: Keep out of the reach of children.
P261: Avoid inhaling dust/fume/gas/mist/vapour/spray.
P280: Use protective gloves/protective clothing/respiratory protection.
P302+P352: IF CHEMICAL COMES IN CONTACT WITH SKIN: Wash with plenty of soap and water
P501: Dispose of the contents/packaging in accordance with local legislation.
Supplemental hazard information:
EUH066: Repeated exposure may cause drying or cracking of the skin.
Substances affecting the classification
Bis(2-ethylhexanoate) cobalt
- 2.3 Other hazards:**
The product does not meet PBT/vPvB criteria.
The product does not meet the criteria for endocrine disrupting properties.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

- 3.1 Substances:**
Not applicable

- CONTINUES ON THE NEXT PAGE -



Uula Floor Paint
Uula Door and Window Paint

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

3.2 Mixtures:

Description: Oil(s)

Ingredients:

In accordance with Annex II (section 3) of Regulation (EC) No 1907/2006 (REACH), the product contains the following substances

Identification	Chemical name/Classification	Concentration
CAS: Not applicable EC: 918-481-9 Index: Not applicable REACH: 01-2119457273-39-XXXX	Hydrocarbons, C10-C13-n-alkanes, isoalkanes, cyclic, with <2% aromatics⁽¹⁾ Self-classified Regulation (EC) No 1272/2008 Asp. Tox. 1: H304; EUH066 - Hazard	30 - <35%
CAS: 64742-95-6 EC: 918-668-5 Index: Not applicable REACH: 01-2119455851-35-XXXX	Hydrocarbons, C9, aromatic⁽¹⁾ Self-classified Regulation (EC) No 1272/2008 Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; STOT SE 3: H336; EUH066 - Hazard	3 - <6%
CAS: 22464-99-9 EC: 245-018-1 Index: Not applicable REACH: 01-2119979088-21-XXXX	2-ethylhexanoic acid, zirconium salt⁽¹⁾ Self-classified Regulation (EC) No 1272/2008 Repr. 2: H361d - Warning	<0.25%
CAS: 872-50-4 EC: 212-828-1 Index: 606-021-00-7 REACH: 01-2119472430-46-XXXX	N-methyl-2-pyrrolidone⁽¹⁾ ATP ATP09 Regulation (EC) No 1272/2008 Eye Irrit. 2: H319; Repr. 1B: H360D; Skin Irritant. 2: H315; STOT SE 3: H335 - Danger	<0.2%
CAS: 136-52-7 EC: 205-250-6 Index: Not applicable REACH: 01-2119524678-29-XXXX	Bis(2-ethylhexanoate) cobalt⁽¹⁾ Self-classified Regulation (EC) No 1272/2008 Aquatic Acute 1: H400; Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Repr. 1B: H360; Skin Sens. 1A: H317 - Danger	<0.15%
CAS: 77-99-6 EC: 201-074-9 Index: Not applicable REACH: 01-2119486799-10-XXXX	Propylidinetrimethanol⁽¹⁾ Self-classified Regulation (EC) No 1272/2008 Repr. 2: H361fd - Warning	<0.15%
CAS: 108-65-6 EC: 203-603-9 Index: 607-195-00-7 REACH: 01-2119475791-29-XXXX	2-methoxy-1-methyl ethyl acetate⁽²⁾ Self-classified Regulation (EC) No 1272/2008 Flam. Liq. 3: H226; STOT SE 3: H336 - Warning	<0.02%
CAS: 78-93-3 EC: 201-159-0 Index: 606-002-00-3 REACH: 01-2119457290-43-XXXX	Butanone⁽²⁾ ATP CLP00 Regulation (EC) No 1272/2008 Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Hazard	<0.01%

⁽¹⁾ A substance dangerous to health or the environment that meets the criteria set in Regulation (EU) No 2020/878.

⁽²⁾ A substance for which an occupational exposure limit value has been set in the European Union

For more information on the hazardous nature of the substances, see sections 11, 12 and 16.

Other information:

Identification	Specific concentration limit
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	percentage by weight >=10: STOT SE 3 - H335

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

Poisoning may result in symptoms after exposure and therefore when in doubt, after direct exposure to the chemical and if malaise persists, seek medical attention and show the safety data sheet for this product.

Inhalation:

This product does not contain substances classified as dangerous if inhaled. However, if symptoms of poisoning occur, it is recommended that the exposed person be taken away from the exposure area to fresh air and kept at rest. Medical attention should be sought if symptoms persist.

Skin contact:

- CONTINUES ON THE NEXT PAGE -



Uula Floor Paint
Uula Door and Window Paint

SECTION 4: FIRST AID MEASURES (continued)

Take off contaminated clothes and shoes, rinse the skin and, if possible, spray the exposed area with plenty of water and neutral soap. If exposure is significant, seek medical attention. If the mixture causes burns or frostbite, do not remove clothing that has adhered to the skin, as this may aggravate the injury. If blisters form on the skin, they should not be punctured as this increases the risk of inflammation.

Eye contact:

Rinse your eyes with plenty of water at room temperature for at least 15 minutes. Avoid closing and rubbing the eyes. To avoid further damage, any contact lenses should be removed from the eyes unless they are stuck to the eyes. In all cases, seek medical attention as soon as possible after flushing and take the product safety data sheet with you.

Ingestion/aspiration:

Do not vomit. If the patient vomits, the head should be kept upright to avoid the risk of aspiration. Keep patient at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

The acute and delayed effects are mentioned in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Preferably use multi-purpose powder extinguishers (ABC powder) or alternatively foam or carbon dioxide (CO₂) extinguishers.

Unsuitable extinguishing media:

It is NOT RECOMMENDED to use a direct water jet for extinguishing.

5.2 Special hazards arising from substances or mixtures:

Thermal decomposition or combustion can produce reaction products that can be highly toxic and therefore cause serious health hazards.

5.3 Advice for firefighters:

Depending on the intensity of the fire, full protective clothing and self-contained breathing apparatus may be required. A minimum level of safety equipment and first aid equipment (fire blankets, first aid kit, etc.) must be available.

Additional provisions:

Act in accordance with the internal emergency plan and the guidelines for dealing with accidents and other emergencies. Remove all sources of ignition. In the event of fire, cool containers and storage tanks containing products that are highly flammable, explosive and prone to BLEVE explosions due to high temperatures. The release of products used in firefighting into aquatic environments must be avoided.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate spills if this does not pose an additional risk to the persons carrying out the task. The area must be evacuated and unprotected persons kept away. Due to potential exposure to spillage, the use of personal protective equipment is mandatory (see section 8). As a priority, the formation of flammable vapour-air mixtures should be avoided, either by ventilation or by using an inert substance. Remove all sources of ignition. Eliminate electrostatic charges by connecting and earthing all conductive surfaces where static electricity can build up.

For emergency responders:

See section 8.

6.2 Environmental precautions:

Every effort must be made to prevent the product from entering aquatic environments. Sucked product must be stored properly in hermetically sealed containers. Exposure to the public or the environment must be reported to the competent authority.

6.3 Methods and material for containment and cleaning up:

Recommended measures:

- CONTINUES ON THE NEXT PAGE -



Uula Floor Paint
Uula Door and Window Paint

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Soak the spill in sand or non-reactive absorbent and move it to a safe place. Do not absorb the substance into sawdust or other flammable absorbents. For more information on the disposal of the product, see section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions

Comply with existing legislation on the prevention of work-related risks. Storage containers must be kept hermetically sealed. Be prepared for spills and product residues, dispose of them safely (section 6). Avoid free spillage from the container. The area where dangerous products are handled must be kept organised and clean.

B.- Technical recommendations for the prevention of fires and explosions

Avoid evaporation of the product as it contains flammable substances which may form flammable vapour-air mixtures in the vicinity of ignition sources. Ignition sources (mobile phones, sparks, etc.) must be controlled, and the transfer from one container to another must be done slowly to avoid the build-up of electrostatic charges. For more information on conditions and substances to avoid, see section 10.

C.- Technical recommendations for the prevention of ergonomic and toxicological risks

Do not eat or drink when handling the product and wash your hands with appropriate cleaning products after handling.

D.- Technical recommendations for the prevention of environmental risks

Due to the hazardous nature of the product to the environment, it is recommended to handle it in an area that is sumped or fenced off from spills and to keep an absorbent in the vicinity of the product.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage:

Store in a cool, dry and ventilated place

B.- General storage conditions

Avoid heat and radiation sources, static electricity and contact with food. See section 10.5 for more information.

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendations regarding the use of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances for which occupational exposure limit values must be monitored in the workplace:

HTP values 2020:

Identification	Occupational exposure limits		
	HTP (8h)		
Quartz (RCS < 1%) CAS: 14808-60-7 EC: 238-878-4	HTP (8h)		0.05 mg/m ³
	HTP (15 min)		
2-methoxy-1-methylethylacetate CAS: 108-65-6 EC: 203-603-9	HTP (8h)	50 ppm	270 mg/m ³
	HTP (15 min)	100 ppm	550 mg/m ³
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	HTP (8h)	3.5 ppm	14 mg/m ³
	HTP (15 min)	20 ppm	80 mg/m ³
Ethanol CAS: 64-17-5 EC: 200-578-6	HTP (8h)	1,000 ppm	1,900 mg/m ³
	HTP (15 min)	1,300 ppm	2,500 mg/m ³
Propane-2-ol CAS: 67-63-0 EC: 200-661-7	HTP (8h)	200 ppm	500 mg/m ³
	HTP (15 min)	250 ppm	620 mg/m ³
Butanone CAS: 78-93-3 EC: 201-159-0	HTP (8h)	20 ppm	60 mg/m ³
	HTP (15 min)	100 ppm	300 mg/m ³

Biological limits:

- CONTINUES ON THE NEXT PAGE -



Uula Floor Paint
Uula Door and Window Paint

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

HTP values 2020

Identification	Threshold value	Parameter	Sampling time
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	25 mg/g (NULL)	Urinary 5-Hydroxy-N-methyl-2-pyrrolidone	At the end of work shift

DNEL (Workers):

Identification		Short-term exposure		Long-term exposure	
		Systematic	Local	Systematic	Local
Hydrocarbons, C9, aromatic CAS: 64742-95-6 EC: 918-668-5	Oral	Not applicable	Not applicable	Not applicable	Not applicable
	Dermal	Not applicable	Not applicable	25 mg/kg	Not applicable
	Inhalation	Not applicable	Not applicable	150 mg/m ³	Not applicable
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	Oral	Not applicable	Not applicable	Not applicable	Not applicable
	Dermal	Not applicable	Not applicable	6.49 mg/kg	Not applicable
	Inhalation	Not applicable	Not applicable	32.97 mg/m ³	Not applicable
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	Oral	Not applicable	Not applicable	Not applicable	Not applicable
	Dermal	Not applicable	Not applicable	4.8 mg/kg	Not applicable
	Inhalation	Not applicable	Not applicable	14.4 mg/m ³	40 mg/m ³
Bis(2-ethylhexanoate) cobalt CAS: 136-52-7 EC: 205-250-6	Oral	Not applicable	Not applicable	Not applicable	Not applicable
	Dermal	Not applicable	Not applicable	Not applicable	Not applicable
	Inhalation	Not applicable	Not applicable	Not applicable	0.2351 mg/m ³
Propylidinetrimethanol CAS: 77-99-6 EC: 201-074-9	Oral	Not applicable	Not applicable	Not applicable	Not applicable
	Dermal	Not applicable	Not applicable	0.94 mg/kg	Not applicable
	Inhalation	Not applicable	Not applicable	3.3 mg/m ³	Not applicable
2-Methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Not applicable	Not applicable	Not applicable	Not applicable
	Dermal	Not applicable	Not applicable	796 mg/kg	Not applicable
	Inhalation	Not applicable	550 mg/m ³	275 mg/m ³	Not applicable
Butanone CAS: 78-93-3 EC: 201-159-0	Oral	Not applicable	Not applicable	Not applicable	Not applicable
	Dermal	Not applicable	Not applicable	1.161 mg/kg	Not applicable
	Inhalation	Not applicable	Not applicable	600 mg/m ³	Not applicable

DNEL (General Public):

Identification		Short-term exposure		Long-term exposure	
		Systematic	Local	Systematic	Local
Hydrocarbons, C9, aromatic CAS: 64742-95-6 EC: 918-668-5	Oral	Not applicable	Not applicable	11 mg/kg	Not applicable
	Dermal	Not applicable	Not applicable	11 mg/kg	Not applicable
	Inhalation	Not applicable	Not applicable	32 mg/m ³	Not applicable
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	Oral	Not applicable	Not applicable	4.51 mg/kg	Not applicable
	Dermal	Not applicable	Not applicable	3.25 mg/kg	Not applicable
	Inhalation	Not applicable	Not applicable	8.13 mg/m ³	Not applicable
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	Oral	Not applicable	Not applicable	0.85 mg/kg	Not applicable
	Dermal	Not applicable	Not applicable	2.4 mg/kg	Not applicable
	Inhalation	Not applicable	Not applicable	3.6 mg/m ³	4.5 mg/m ³
Bis(2-ethylhexanoate) cobalt CAS: 136-52-7 EC: 205-250-6	Oral	Not applicable	Not applicable	0.175 mg/kg	Not applicable
	Dermal	Not applicable	Not applicable	Not applicable	Not applicable
	Inhalation	Not applicable	Not applicable	Not applicable	0.037 mg/m ³
Propylidinetrimethanol CAS: 77-99-6 EC: 201-074-9	Oral	Not applicable	Not applicable	0.34 mg/kg	Not applicable
	Dermal	Not applicable	Not applicable	0.34 mg/kg	Not applicable
	Inhalation	Not applicable	Not applicable	0.58 mg/m ³	Not applicable
2-Methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Not applicable	Not applicable	36 mg/kg	Not applicable
	Dermal	Not applicable	Not applicable	320 mg/kg	Not applicable
	Inhalation	Not applicable	Not applicable	33 mg/m ³	33 mg/m ³
Butanone CAS: 78-93-3 EC: 201-159-0	Oral	Not applicable	Not applicable	31 mg/kg	Not applicable
	Dermal	Not applicable	Not applicable	412 mg/kg	Not applicable
	Inhalation	Not applicable	Not applicable	106 mg/m ³	Not applicable

- CONTINUES ON THE NEXT PAGE -



Uula Floor Paint
Uula Door and Window Paint

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

PNEC:

Identification				
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	STP	10 mg/L	Fresh water	0.25 mg/L
	Soil	0.07 mg/kg	Marine water	0.025 mg/L
	Intermittent	5 mg/L	Sediment (Fresh water)	1.09 mg/kg
	Oral	Not applicable	Sediment (Marine water)	0.109 mg/kg
Bis(2-ethylhexanoate) cobalt CAS: 136-52-7 EC: 205-250-6	STP	0.37 mg/L	Fresh water	0.00062 mg/L
	Soil	10.9 mg/kg	Marine water	0.00236 mg/L
	Intermittent	Not applicable	Sediment (Fresh water)	53.8 mg/kg
	Oral	Not applicable	Sediment (Marine water)	69.8 mg/kg
2-Methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	STP	100 mg/L	Fresh water	0.635 mg/L
	Soil	0.29 mg/kg	Marine water	0.064 mg/L
	Intermittent	6.35 mg/L	Sediment (Fresh water)	3.29 mg/kg
	Oral	Not applicable	Sediment (Marine water)	0.329 mg/kg
Butanone CAS: 78-93-3 EC: 201-159-0	STP	709 mg/L	Fresh water	55.8 mg/L
	Soil	22.5 mg/kg	Marine water	55.8 mg/L
	Intermittent	55.8 mg/L	Sediment (Fresh water)	284.74 mg/kg
	Oral	1 g/kg	Sediment (Marine water)	284.7 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventive measure, the use of "CE marked" personal protective equipment is recommended. For more information on personal protective equipment (storage, use, cleaning, maintenance, protection class, etc.), see the brochures provided by the manufacturers. The instructions given here apply to the product as such. The safety procedures for a diluted product may vary depending on the degree of dilution, the use, the method used, etc. When determining the obligation to install emergency showers and/or eye rinsing equipment in storage areas, the applicable regulations for the storage of chemical products will be taken into account. See sections 7.1 and 7.2 for more information.

B.- Respiratory protection

The use of personal protective equipment is necessary if the substance produces a mist or if occupational exposure limit values are exceeded.

C.- Hand protection

Not applicable

D.- Eye and face protection

Not applicable

E.- Body protection

Not applicable

F.- Additional emergency measures

No additional emergency measures are necessary.

Environmental exposure controls:

Under community legislation on environmental protection, it is recommended to avoid throwing the product and its packaging into the environment. See section 7.1.D. for more information.

Volatile organic compounds:

In accordance with Directive 2010/75/EU, the product has the following characteristics:

VOCs (delivery):	37.65% by weight
VOC content at 20 °C:	397.5 kg/m ³ (397.5 g/L)
Average carbon number:	11.37
Average molecular weight:	127.05 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

*Not applicable due to product characteristics, no information on product hazards.

- CONTINUES ON THE NEXT PAGE -



Uula Floor Paint
Uula Door and Window Paint

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

9.1 Information on basic physical and chemical properties:

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Viscous
Colour:	According to the labelling
Odour:	Solvent
Odour threshold:	Not applicable *

Volatility:

Boiling temperature at normal pressure:	Not applicable *
Vapour pressure at 20 °C:	Not applicable *
Vapour pressure at 50 °C:	Not applicable *
Evaporation rate at 20 °C:	Not applicable *

Product description:

Density at 20 °C:	1,055.7 kg/m ³
Relative density at 20 °C:	1.056
Dynamic viscosity at 20 °C:	Not applicable *
Kinematic viscosity at 20 °C:	Not applicable *
Kinematic viscosity at 40 °C:	>20.5 mm ² /s
Concentration:	Not applicable *
pH:	Not applicable *
Vapour density at 20 °C:	Not applicable *
Partition coefficient n-octanol/water at 20 °C:	Not applicable *
Solubility in water at 20 °C:	Not applicable *
Solubility properties:	Insoluble in water
Decomposition temperature:	Not applicable *
Melting point/freezing point:	Not applicable *

Flammability:

Flash point:	> 61 °C
Flammability (solid, gas):	Not applicable *
Auto-ignition temperature:	230 °C
Lower flammability limit:	Not applicable *
Upper flammability limit:	Not applicable *

Particle characteristics:

Median equivalent diameter:	Not applicable
-----------------------------	----------------

9.2 Other information:

Information with regard to physical hazard classes:

Explosiveness:	Not applicable *
Flammability:	Not applicable *
Metal-corrosive substances and mixtures:	Not applicable *
Combustion temperature:	Not applicable *
Total percentage (by mass) of aerosol-flammable components:	Not applicable *

Other safety characteristics:

Surface tension at 20 °C:	Not applicable *
---------------------------	------------------

*Not applicable due to product characteristics, no information on product hazards.

- CONTINUES ON THE NEXT PAGE -



Uula Floor paint
Uula Door and Window paint

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Refractive index: Not applicable *

*Not applicable due to product characteristics, no information on product hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected if the technical instructions for the storage of chemicals are followed. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of use, handling and storage specified in the instructions.

10.3 Possibility of hazardous reactions:

No hazardous reactions leading to excessive temperatures or pressure are expected under the conditions specified in the instructions.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precautionary measure	Precautionary measure	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising substances	Flammable substances	Other
Avoid strong acids	Not applicable	Avoid	Not applicable	Avoid strong bases

10.6 Hazardous decomposition products:

See sections 10.3, 10.4 and 10.5 for a detailed description of the decomposition products. Depending on the conditions of decomposition, complex mixtures of chemical substances may be released as a result of decomposition: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

There is no experimental evidence-based data on the toxicological properties of the mixture

Hazardous health effects:

If exposure is repeated, prolonged or exceeds the occupational exposure limit values, the product may have adverse health effects depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on the available information, the classification criteria are not met, and the product does not contain any substances classified as dangerous in terms of ingestion. See section 3 for more information.
- Corrosivity/Irritability: Based on the available information, the classification criteria are not met, but the product does contain substances classified as dangerous in terms of this effect. For more information, see section 3.

B- Inhalation (acute effect):

- Acute toxicity: Based on the available information, the classification criteria are not met, and the product does not contain any substances classified as dangerous if inhaled. See section 3 for more information.
- Corrosivity/Irritability: Based on the available information, the classification criteria are not met, but the product does contain substances classified as dangerous if inhaled. See section 3 for more information.

C- Skin and eye contact (acute effect):

- Skin contact: Based on the available information, the classification criteria are not met, but the product does contain substances classified as dangerous if in contact with the skin. See section 3 for more information.
- Eye contact: Based on the available information, the classification criteria are not met, but the product does contain substances classified as dangerous in terms of this effect. For more information, see section 3.

D- CMR effects (carcinogenicity, mutagenicity and reproductive toxicity):

- CONTINUES ON THE NEXT PAGE -



Uula Floor paint
Uula Door and Window paint

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Carcinogenicity: Based on the available information, the classification criteria are not met, and the product does not contain any substances classified as dangerous in terms of this effect. See section 3 for more information.
IARC: Hydrocarbons, C9, aromatic (3); Polypropylene (3); Polyethylene (3); polytetrafluoroethylene (3); Naphtha (petroleum), sulfur-free heavy (3); Bis(2-ethylhexanoate) cobalt (2B); Ethanol (1); Propan-2-ol (3)
- Mutagenicity: Based on the available information, the classification criteria are not met, and the product does not contain any substances classified as dangerous in terms of this effect. For more information, see section 3.
- Reproductive toxicity: Based on the available information, the classification criteria are not met, but the product does contain substances classified as dangerous in terms of this effect. For more information, see section 3.

E- Sensitisation:

- Inhalation: Based on the available information, the classification criteria are not met, and the product does not contain any substances classified as dangerous in terms of sensitisation. See section 3 for more information.
- Skin contact: Long-term skin contact can cause allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Based on the available information, the classification criteria are not met, but the product does contain substances classified as dangerous if inhaled. See section 3 for more information.

G- Specific target organ toxicity (STOT) - repeated exposure:

- Specific target organ toxicity (STOT) - repeated exposure: Based on the available information, the classification criteria are not met, and the product does not contain any substances classified as dangerous in terms of this effect. For more information, see section 3.
- Skin contact: Repeated exposure may cause drying or cracking of the skin.

H- Aspiration:

Based on the available information, the classification criteria are not met, but the product does contain substances classified as dangerous in terms of this effect. For more information, see section 3.

Other information:

Not applicable

Information on the toxicity of substances:

Identification	Acute toxicity		Genus
	LD50 Oral	LD50 Dermal	
Hydrocarbons, C10-C13-n-alkanes, isoalkanes, cyclic, with <2% aromatics CAS: Not applicable EC: 918-481-9	>2,000 mg/kg	>2,000 mg/kg	
		>20 mg/L	
Hydrocarbons, C9, aromatic CAS: 64742-95-6 EC: 918-668-5	>2,000 mg/kg	>2,000 mg/kg	
		>20 mg/L	
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	2,043 mg/kg	>2,000 mg/kg	Rat
		>5 mg/L	
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	>5,000 mg/kg	>5,000 mg/kg	Rat
		>20 mg/L	Rat
Bis(2-ethylhexanoate) cobalt CAS: 136-52-7 EC: 205-250-6	>2,000 mg/kg	>2,000 mg/kg	
		>5 mg/L	
Propylidinetrimethanol CAS: 77-99-6 EC: 201-074-9	>2,000 mg/kg	>2,000 mg/kg	
		>5 mg/L	
2-Methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	8,532 mg/kg	>5,000 mg/kg	Rat
		30 mg/L (4 h)	Rat
Butanone CAS: 78-93-3 EC: 201-159-0	4,000 mg/kg	6,400 mg/kg	Rat
		23.5 mg/L (4 h)	Rabbit
			Rat

Estimate of acute toxicity (ATE mix):

ATE mix	Ingredients with unknown toxicity
---------	-----------------------------------

- CONTINUES ON THE NEXT PAGE -



Uula Floor paint
Uula Door and Window paint

Oral	>2,000 mg/kg (Calculation method)	Not applicable
Dermal	>2,000 mg/kg (Calculation method)	Not applicable
Inhalation	20 mg/L (4 h) (Calculation method)	Not applicable

11.2 Information on other hazards:

Endocrine disruptive properties

The product does not meet the criteria for endocrine disrupting properties.

Other information

Not applicable

SECTION 12: ECOLOGICAL INFORMATION

There is no experimental evidence-based information on the environmental hazards of the mixture.

12.1 Toxicity:

Acute toxicity:

Identification	Concentration	Species	Genus
Hydrocarbons, C9, aromatic CAS: 64742-95-6 EC: 918-668-5	LC50	>1 - 10 (96 h)	Fish
	EC50	>1 - 10 (48 h)	Crustacean
	EC50	>1 - 10 (72 h)	Seaweed
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	LC50	270 mg/L (96 h)	N/A
	EC50	Not applicable	
	EC50	Not applicable	
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	LC50	832 mg/L (96 h)	Lepomis macrochirus
	EC50	4,897 mg/L (48 h)	Daphnia magna
	EC50	500 mg/L (72 h)	Scenedesmus subspicatus
Bis(2-ethylhexanoate) cobalt CAS: 136-52-7 EC: 205-250-6	LC50	>0.1 - 1 (96 h)	Fish
	EC50	>0.1 - 1 (48 h)	Crustacean
	EC50	>0.1 - 1 (72 h)	Seaweed
2-methoxy-1-methylethylacetate CAS: 108-65-6 EC: 203-603-9	LC50	161 mg/L (96 h)	Pimephales promelas
	EC50	481 mg/L (48 h)	Daphnia sp.
	EC50	Not applicable	
Butanone CAS: 78-93-3 EC: 201-159-0	LC50	3,220 mg/L (96 h)	Pimephales promelas
	EC50	5,091 mg/L (48 h)	Daphnia magna
	EC50	4,300 mg/L (168 h)	Scenedesmus quadricauda

Chronic toxicity:

- CONTINUES ON THE NEXT PAGE -



Uula Floor paint
Uula Door and Window paint

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Concentration		Species	Genus
	NOEC			
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	NOEC	Not applicable		
	NOEC	25 mg/L	Daphnia magna	Crustacean
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	NOEC	Not applicable		
	NOEC	12.5 mg/L	Daphnia magna	Crustacean
Bis(2-ethylhexanoate) cobalt CAS: 136-52-7 EC: 205-250-6	NOEC	0.21 mg/L	Pimephales promelas	Fish
	NOEC	0.1697 mg/L	Aeolosoma sp.	Crustacean
2-methoxy-1-methylethylacetate CAS: 108-65-6 EC: 203-603-9	NOEC	47.5 mg/L	Oryzias latipes	Fish
	NOEC	100 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	BOD5	Not applicable	Concentration	20 mg/L
	COD	Not applicable	Duration	28 days
	BOD5/COD	Not applicable	%Biodegradable	99%
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	BOD5	1.09 g O2/g	Concentration	100 mg/L
	COD	1.6 g O2/g	Duration	28 days
	BOD5/COD	0.68	%Biodegradable	73%
2-Methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BOD5	Not applicable	Concentration	785 mg/L
	COD	Not applicable	Duration	8 days
	BOD5/COD	Not applicable	%Biodegradable	100%
Butanone CAS: 78-93-3 EC: 201-159-0	BOD5	2.03 g O2/g	Concentration	Not applicable
	COD	2.31 g O2/g	Duration	20 days
	BOD5/COD	0.88	%Biodegradable	89%

12.3 Bioaccumulative potential:

Identification	Bioaccumulative potential	
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	BCF	
	Log POW	2.96
	Potential	
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	BCF	0.23
	Log POW	-0.46
	Potential	Low
2-methoxy-1-methylethylacetate CAS: 108-65-6 EC: 203-603-9	BCF	1
	Log POW	0.43
	Potential	Low

- CONTINUES ON THE NEXT PAGE -



Uula Floor paint
Uula Door and Window paint

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Bioaccumulative potential	
Butanone CAS: 78-93-3 EC: 201-159-0	BCF	3
	Log POW	0.29
	Potential	Low

12.4 Mobility in soil:

Identification	Absorption and/or desorption		Volatility	
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	Koc	Not applicable	Henry	2.94E-1 Pa·m ³ /mol
	Conclusion	Not applicable	Dry land	Yes
	Surface tension	Not applicable	Wet land	Yes
N-methyl-2-pyrrolidone CAS: 872-50-4 EC: 212-828-1	Koc	Not applicable	Henry	Not applicable
	Conclusion	Not applicable	Dry land	Not applicable
	Surface tension	4.007E-2 N/m (25 °C)	Wet land	Not applicable
Propylidinetrimethanol CAS: 77-99-6 EC: 201-074-9	Koc	Not applicable	Henry	Not applicable
	Conclusion	Not applicable	Dry land	Not applicable
	Surface tension	2.357E-2 N/m (246.93 °C)	Wet land	Not applicable
Butanone CAS: 78-93-3 EC: 201-159-0	Koc	30	Henry	5.77 Pa·m ³ /mol
	Conclusion	Very high	Dry land	Yes
	Surface tension	2.396E-2 N/m (25 °C)	Wet land	Yes

12.5 Results of PBT and vPvB assessment:

The product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

The product does not meet the criteria for endocrine disrupting properties.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Commission Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances	Dangerous

Type of waste (Commission Regulation (EU) No 1357/2014):

HP14 Dangerous for the environment

Waste management (disposal and evaluation):

Talk to your licensed waste handler about recovery and disposal in accordance with Annexes 1 and 2 (Directive 2008/98/EC). In accordance with Codes 15 01 (2014/955/EU), if the packaging has been in direct contact with the product, it should be treated in the same way as the product, otherwise it should be treated as non-hazardous waste. Discharge into drains is not recommended. See section 6.2.

Legislation on waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH), community or country-specific provisions relating to waste management are indicated.

Community legislation: Directive 2008/98/EC, 2014/955/EU, Commission Regulation (EU) No 1357/2014

National legislation: Waste Act, 646/2011, 1104/2011, 195/2015, 1178/2013, 25/2014, 410/2014, 528/2014

SECTION 14: TRANSPORT INFORMATION

The product is not subject to the transport regulations for dangerous goods. (ADR/RID, IMDG, IATA)

SECTION 15: REGULATORY INFORMATION

- CONTINUES ON THE NEXT PAGE -



Uula Floor paint
Uula Door and Window paint

SECTION 15: REGULATORY INFORMATION (continued)

15.1 Safety, health and environmental regulations/legislations specific for the substance or mixture:

List of substances of very high concern under Regulation (EC) No 1907/2006 (REACH): N-methyl-2-pyrrolidone

Substances included in Annex XIV of the REACH list (authorisation list) and expiry date: Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer: Not applicable

Article 95, REGULATION (EU) No 528/2012: Not applicable

REGULATION (EU) No 649/2012 concerning the export and import of dangerous chemicals: Not applicable

Seveso III:

Not applicable

Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and products (REACH, Annex XVII, etc...):

Not to be used in:

-decorative items intended to produce light or colour effects using different phases, such as decorative lamps and ashtrays,
-tricks and jokes,

-games intended for one or more participants or in any item intended for that purpose which is also decorative.

Contains the substance N-methyl-2-pyrrolidone. 1. | Shall not be placed on the market as a substance on its own or in mixtures at a concentration equal to or greater than 0.3 percent after May 9, 2020, except if manufacturers, importers and downstream users have included in the relevant chemical safety reports and safety data sheets derived no effect exposure levels (DNELs) for worker exposure at a level of 14.4 mg/m³ by inhalation and 4.8 mg/kg/day by skin. | 2. | Shall not be used as a substance on its own or in mixtures at a concentration equal to or greater than 0.3 percent after May 9, 2020, unless manufacturers and downstream users implement appropriate risk management measures and provide the necessary operating conditions to ensure that worker exposure is below the DNELs defined in section 1. | 3. | Deviating from what is stipulated in sections 1 and 2, the obligations stipulated in them apply to placing on the market for use or for use as a solvent or starting material in the coating of wires from May 9, 2024.

Occupational exposure to respirable crystalline silica shall be controlled in accordance with Directive (EU) 2019/130.

Special provisions for the protection of people and the environment:

It is recommended that the information contained in this safety data sheet should be used as a starting point for assessing the risks arising from local conditions in order to determine the necessary risk control measures for the handling, use, storage and disposal of this product.

Other legislation:

Chemicals Act 599/2013

Chemicals Act 746/2016 62 §.

Decree on the names of substances (in Finnish/Swedish) 5/2010, amendment 1123/2010

Government Decree on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products 837/2005, as amended 813/2010, 6/2011, 269/2012

Government Decree on the limitation of emissions into the air from certain activities and installations using organic solvents (64/2015), amended by Decree 167/2018

Waste Act 646/2011, as amended Government Decree on Waste (179/2012)

Transport of Dangerous Goods Act (719/1994, amendment 1541/2019)

Government Decree on the transport of dangerous goods by road (194/2002, amendment 578/2021)

Government Decree on the demonstration of conformity of packaging, containers and bulk containers intended for the transport of dangerous goods and on the inspection bodies performing related tasks (124/2015, amendment 778/2015)

15.2 Chemical safety assessment:

The supplier has not carried out a chemical safety assessment.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been prepared in accordance with Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878), Annex II (Guide to the compilation of safety data sheets).

Changes to the safety data sheet that affect risk management measures:

- CONTINUES ON THE NEXT PAGE -



Uula Floor paint
Uula Door and window paint



SECTION 16: OTHER INFORMATION (continued)

Not applicable

Texts of the legislative clauses in section 2:

H412: Harmful to aquatic organisms with long-term adverse effects.

H317: May cause an allergic skin reaction.

Texts of the legislative clauses in section 3:

These statements are not related to the product itself, they are given for information and refer to the components mentioned in section 3.

CLP Regulation (EC) No 1272/2008:

Aquatic Acute 1: H400 - Very toxic to aquatic organisms.

Aquatic Chronic 2: H411 - Very toxic to aquatic organisms with long-term adverse effects.

Aquatic Chronic 3: H412 - Harmful to aquatic organisms with long-term adverse effects.

Asp. Tox. 1: H304 - May be fatal if ingested and inhaled.

Eye Irrit. 2: H319 - Very irritating to eyes.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Repr. 1B: H360 - May impair fertility or damage the foetus.

Repr. 1B: H360D - May damage the foetus.

Repr. 2: H361d - Suspected of damaging the foetus.

Repr. 2: H361fd - Suspected of impairing fertility. Suspected of damaging the foetus.

Skin Irritant. 2: H315 - Irritates the skin.

Skin Sens. 1A: H317 - May cause an allergic skin reaction.

STOT SE 3: H335 - May cause respiratory tract irritation.

STOT SE 3: H336 - May cause drowsiness and dizziness.

Classification procedure:

Aquatic Chronic 3: Calculation method

Skin Sens. 1A: Calculation method

Advice on training:

It is recommended that persons handling this product have a minimum level of training in occupational safety and prevention measures to facilitate understanding and interpretation of this safety data sheet and product labelling.

Main sources of information:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

Abbreviations:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International Maritime Dangerous Goods Code

IATA: The International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical oxygen demand

BOD5: Biological oxygen demand over 5 days

BCF: Bioconcentration factor

LD50: Lethal dose 50, at which half of the test animals die

LC50: Lethal concentration 50, at which half of the test animals die

EC50: Effective concentration 50, at which an effect is observed in half of the cases

Log Pow: Octanol/water partition coefficient

Koc: Organic hydrocarbon partition coefficient

UFI: Unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, scientific and technical knowledge and current national and EU legislation, but does not guarantee its accuracy. This information is intended to promote the safe use of the product and the information contained herein cannot be considered as a guarantee of the properties of the product. We do not know or control the working methods or conditions of those using the product, and it is always ultimately the responsibility of the user to take the necessary measures to ensure compliance with applicable regulations when handling, storing, using and disposing of chemicals. The information on this safety data sheet applies only to this product, which must not be used for any other purposes than those specified.

- END OF THE SAFETY DATA SHEET -